

680 300 - 366 726



DIESEL METERS

680 300 Diesel meter with mechanical 3 digit register, 100 l/min

Nutating-disk meter for diesel with mechanical register. Reliable, easy to install and simple to calibrate. Very low pressure drop; it can also be used for gravity fed applications. Resettable partial reading up to 999,9 litres and permanent 6 digit totaliser.

1" BSP (F) and inlet and outlet, both with flange for optional flange mounting. The meter allows the inlet and outlet axis to be orientated in four different positions with respect to the register orientation. Maximum working pressure: 10 Bar. Flow range: 10 to 100 l/minute. Precision after calibration: $\pm 1\%$
Meter valid for non commercial applications only.

680 301 Diesel meter with mechanical 4 digit register, 100 l/min

Similar to model 680 300, but with 4 digit register.

366 726 In-line volume meter with electronic digital display, 100 l/min

Oval gear meter with electronic digital register for diesel and lubricants up to SAE 240. Reliable, easy to install and simple to calibrate. Resettable partial reading up to 999,9 litres and permanent 6 digits totaliser.

Fluid inlet/outlet: 1" BSP (F). Maximum working pressure: 70 bar. Flow range: 9,5 l/min to 100 l/min Precision after calibration: $\pm 0.5\%$. Meter works with two AAA 1,5 V alkaline batteries.

DIESEL PUMP ACCESSORIES

361 000 - 688 001



NOZZLES

361 000 Aluminium manual nozzle

Fluid inlet: 1" BSP (F). Maximum delivery: 100 l/min Includes inlet swivel and lockable trigger.

688 300 Automatic nozzle 60 l/min

Fluid inlet: 1" BSP (F). Maximum delivery: 60 l/min.

688 001 Automatic nozzle 80 l/min

Fluid inlet: 1" BSP (F). Maximum delivery: 80 l/min Includes inlet swivel.

364 030 Inlet swivel

For 1" BSP (F) nozzles. Inlet/outlet threads: 1" BSP (FM).

HOSES

Rubber hoses with swaged terminals, 1" BSP (M).

689 021, 4 m x 19 mm delivery hose**689 022, 4 m x 25 mm delivery hose**

689 036



SUCTION ACCESSORIES

Suction hoses

Rubber suction hoses with foot valve. Connection thread 1" BSP (M).

689 030, 25 mm x 2 m Suction hose**689 031, 25 mm x 4 m Suction hose****Telescopic suction tubes**

Telescopic suction tubes for connecting directly to the pump inlet. 1" BSP (M) connection, 2" (M) bung adaptor and foot valve with filter.

689 035 Telescopic suction tube, 1.000 mm

For drums or tanks with a maximum height of 900 mm.

689 036 Telescopic suction tube, 1.800 mm

For tanks with a maximum height between 1.000 and 1.800 mm.

689 037 Suction attachment

2 m x 25 mm hose connecting to 1.000 mm / 1.800 mm telescopic suction tube.